

CRUISE Inox Clean Touch Marine Refrigerators

The latest development of the world-wide appreciated Elegance product line



isotherm

The Inox Clean Touch represents the latest development of the world-wide appreciated Elegance product line. It combines in fact the Cruise Elegance line features (except Vent-Lock system) with a new door design in stainless steel especially treated to avoid fingerprints (inox anti-fingerprint). This new material combines a state of the art marine design with a very easy cleaning and maintenance of the refrigerator. The Elegance line handle is nicely flush mounted into a new door and centrally located to allow easy switch of the hinge opening side.

- 5 volumes; 42, 49, 65, 85, 130liters
- 3 sides flush mounting frame as standard, 4th side as optional
- High quality stainless steel balcony profiles
- Ready for Isotherm Smart Energy Control & ITC
- Easy fix installation solution
- Reliability: Secop compressors
- Extra-thick insulation for low power consumption
- White LED internal light

Technical specifications

Type	Gross volume (l)	Dimensions H x W x D (mm)	Available with SEC and ITC	Weight (kg)	Power consumption (W/24 hours)	Danfoss/Secop compressor type	Freezer -6°C/21°F volume in l
CR 42 Inox Clean Touch	42	525 x 400 x 500*	X	11,9	285	BD1.4F	4 (-6°C)
CR 49 Inox Clean Touch	49	525 x 400 x 500	X	17,2	265	BD35F	4 (-6°C)
CR 65 Inox Clean Touch	65	528 x 470 x 520	X	19,1	275	BD35F	4 (-6°C)
CR 85 Inox Clean Touch	85	625 x 495 x 550	X	21,9	368	BD35F	6 (-6°C)
CR 130 Inox Clean Touch	130	750 x 545 x 555	X	23,1	418	BD35F	6 (-6°C)

* Depth 385 mm with remote compressor

Power consumption W / 24 h in operation on 12 Volt with +5 °C in the refrigeration space, ambient temperature +25 °C according to the Standards ISO 15502:2005 and EN 153:2006

Refrigerators manufacturing tolerances -2 / +4 mm

Dimensions include refrigerator's feet

With AC / DC optional kit, depth may increase

According to EN 603335 - 1 regulation, the inside walls of the furniture housing the refrigerator must be distant from the fridge by 20 mm per side and 50 mm from the top

Please refer to the installation manual for further technical / installation details

Most of Isotherm fridges can also benefit from a retrofitted Isotherm Smart Energy Control kit. On some models it reduces battery consumption by up to 50 %

Specification changes may be made without prior notice

Cruise Marine Refrigerators Inox Clean Touch

